



2 Megapixels Long Range IP Camera 10X

Long Range Camera 4.7-47mm Optical zoom with starlight view

- 1/1.8" progressive scan CMOS
- Up to 1920 x 1080 resolution, 30fps 4.7-47mm 10x
- Smart IR, up to 200m IR distance
- Ultra 265, H.265,
- 120dB True WDR
- ROI, Corridor Mode, ONVIF
- AC24V,DC12V,PoE.Wide voltage range of $\pm 25\%$
- IP67
- Smart Functions: Intrusion, cross line, motion detection, Enter and loiter in a pre-defined virtual region, Cross a pre-defined virtual line, Moving within a pre-defined virtual region, Face

- detection, Audio detection, Defocus, Scene Change, Object Left, Object Moving, People counting
- Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication

Specification

Max. Resolution	1920x1080
Material	Cast aluminum
Privacy Mask	Up to 8 areas
Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, FTP, SMTP, SNMP, SIP, QoS
Zoom/Focus	Manual 2.8-12mm
Frame Rate	1080P (1920x1080): Max. 30 fps
S/N	>55 dB
Audio I/O	Audio cable
Shutter	Auto/Manual, 1/6~1/100000s
Sensor	1/2.8", 2 megapixel, progressive scan CMOS
WDR	True WDR up to 120 dB
Audio Compression	G.711
Compatible Integration	ONVIF, API
Working Environment	-35C ~ +60C (-31F ~ 140F), Humidity ? 95% RH(non-condensing)
Video Streaming	3
Min. Illumination	Colour: 0.001Lux (F1.6, AGC ON) 0Lux with IR
Vandal Resistant	IK10
Network	10M/100M Base-TX Ethernet
Reset Button	Supported
IR Range	Up to 100m (328 ft) IR range
Day/Night	IR-cut filter with auto switch (ICR)
Weight	.58kg (1.28lb)
9:16 Corridor Mode	Supported
Edge Storage	Micro SD, up to 128 GB
Alarm I/O	1 / 1
Video Compression	H.265, H.264, MJPEG
Serial Port	1 RS485
Dimensions (L x W x H)	305.5 x104.1 x97.3mm (12.0" x 4.1" x 3.8")
ROI	Supported
Lens	4.7 ~ 47mm; P-Iris, AF automatic focusing and motorized zoom lens
Power	DC12V25%, AC24V25% or PoE (IEEE802.3 at) Power consumption: Max. 15W
OSD	Up to 8 OSDs